

61A Lecture 18

Wednesday, October 16

Announcements

- Homework 6 is due Tuesday 10/22 @ 11:59pm
- Project 3 is due Thursday 10/24 @ 11:59pm
- Midterm 2 is on Monday 10/28 7pm–9pm
- Hog strategy contest winners will be announced on Wednesday 10/16 in lecture

Memoization

Memoization

Idea: Remember the results that have been computed before


```
def memo(f):  
    cache = {}  
    def memoized(n):  
        if n not in cache:  
            cache[n] = f(n)  
        return cache[n]  
    return memoized
```

Keys are arguments that map to return values

Same behavior as f, if f is a pure function

(Demo)

Memoized Tree Recursion



fib_tree(35)

Distinct trees with memoization: 35

Distinct trees without memoization: 18,454,929

Time

The Consumption of Time

Implementations of the same functional abstraction can require different amounts of time to compute their result.

Problem: How many factors does a positive integer n have?

A factor k of n is a positive integer such that n/k is also a positive integer.

`def count_factors(n):`

Time (number of divisions)

Slow: Test each k from 1 through n .

n

Fast: Test each k from 1 to square root n .
For every k , n/k is also a factor!

$\lfloor \sqrt{n} \rfloor$

(Demo)

Space

The Consumption of Space

Which environment frames do we need to keep during evaluation?

Each step of evaluation has a set of **active** environments.

Values and frames in active environments consume memory.


Memory used for other values and frames can be recycled.

Active environments:


- Environments for any function calls currently being evaluated
- Parent environments of functions named in active environments

(Demo)

Fibonacci Memory Consumption



Fibonacci Memory Consumption



Order of Growth

Order of Growth

A method for bounding the resources used by a function by the "size" of a problem

n : size of the problem

$R(n)$: Measurement of some resource used (time or space)

$$R(n) = \Theta(f(n))$$

means that there are positive constants k_1 and k_2 such that

$$k_1 \cdot f(n) \leq R(n) \leq k_2 \cdot f(n)$$

for sufficiently large values of **n** .

Iteration vs Memoized Tree Recursion

Iterative and memoized implementations are not the same.

	Time	Space
<pre>def fib_iter(n): prev, curr = 1, 0 for _ in range(n-1): prev, curr = curr, prev + curr return curr</pre>	$\Theta(n)$	$\Theta(1)$
<pre>@memo def fib(n): if n == 1: return 0 if n == 2: return 1 return fib(n-2) + fib(n-1)</pre>	$\Theta(n)$	$\Theta(n)$

Counting Factors

Order of growth can still be used, even if we can quantify amounts exactly.

Problem: How many factors does a positive integer n have?

A factor k of n is a positive integer such that n/k is also a positive integer.

```
def count_factors(n)"
```

Time

Space

Slow: Test each k from 1 to n .

$\Theta(n)$

$\Theta(1)$

Fast: Test each k from 1 to square root n .
For every k , n/k is also a factor!

$\Theta(\sqrt{n})$

$\Theta(1)$

Exponentiation

Exponentiation

Goal: one more multiplication lets us double the problem size.

```
def exp(b, n):  
    if n == 0:  
        return 1  
    else:  
        return b * exp(b, n-1)
```

$$b^n = \begin{cases} 1 & \text{if } n = 0 \\ b \cdot b^{n-1} & \text{otherwise} \end{cases}$$

```
def square(x):  
    return x*x
```

$$b^n = \begin{cases} 1 & \text{if } n = 0 \\ (b^{\frac{1}{2}n})^2 & \text{if } n \text{ is even} \\ b \cdot b^{n-1} & \text{if } n \text{ is odd} \end{cases}$$

```
def fast_exp(b, n):  
    if n == 0:  
        return 1  
    elif n % 2 == 0:  
        return square(fast_exp(b, n//2))  
    else:  
        return b * fast_exp(b, n-1)
```

(Demo)

Exponentiation

Goal: one more multiplication lets us double the problem size.

	Time	Space
<pre>def exp(b, n): if n == 0: return 1 else: return b * exp(b, n-1)</pre>	$\Theta(n)$	$\Theta(n)$
<pre>def square(x): return x*x</pre>		
<pre>def fast_exp(b, n): if n == 0: return 1 elif n % 2 == 0: return square(fast_exp(b, n//2)) else: return b * fast_exp(b, n-1)</pre>	$\Theta(\log n)$	$\Theta(\log n)$

Comparing Orders of Growth

Comparing orders of growth (n is the problem size)

