

## CS61B Lecture #18

### Today:

- Asymptotic complexity (from last time)
- Overview of standard Java Collections classes.
  - Iterators, ListIterators
  - Containers and maps in the abstract
  - Views

Readings for Today: *Data Structures*, Chapter 2.

Readings for next Topic: *Data Structures*, Chapter 3.

## Some Intuition on Meaning of Growth


- How big a problem can you solve in a given time?
- In the following table, left column shows time in microseconds to solve a given problem as a function of problem size  $N$ .
- Entries show the *size of problem* that can be solved in a second, hour, month (31 days), and century, for various relationships between time required and problem size.
- $N$  = problem size

Time ( $\mu$ sec) for problem size $N$	1 second	Max $N$ Possible in 1 hour	1 month	1 century
$\lg N$	$10^{300000}$	$10^{1000000000}$	$10^{8 \cdot 10^{11}}$	$10^{9 \cdot 10^{14}}$
$N$	$10^6$	$3.6 \cdot 10^9$	$2.7 \cdot 10^{12}$	$3.2 \cdot 10^{15}$
$N \lg N$	63000	$1.3 \cdot 10^8$	$7.4 \cdot 10^{10}$	$6.9 \cdot 10^{13}$
$N^2$	1000	60000	$1.6 \cdot 10^6$	$5.6 \cdot 10^7$
$N^3$	100	1500	14000	150000
$2^N$	20	32	41	51

## New Topic: Data Types in the Abstract

- Most of the time, should *not* worry about implementation of data structures, search, etc.
- What they do for us—their specification—is important.
- Java has several standard types (in `java.util`) to represent collections of objects
  - Six interfaces:
    - \* Collection: General collections of items.
    - \* List: Indexed sequences with duplication
    - \* Set, SortedSet: Collections without duplication
    - \* Map, SortedMap: Dictionaries (key  $\mapsto$  value)
  - Concrete classes that provide actual instances: `LinkedList`, `ArrayList`, `HashSet`, `TreeSet`.
  - To make change easier, purists would use the concrete types only for **new**, interfaces for parameter types, local variables.

## Collection Structures in java.util



## The Collection Interface

- Collection interface. Main functions promised:
  - Membership tests: contains ( $\in$ ), containsAll ( $\subseteq$ )
  - Other queries: size, isEmpty
  - Retrieval: iterator, toArray
  - Optional modifiers: add, addAll, clear, remove, removeAll (set difference), retainAll (intersect)

- Design point (a side trip): Optional operations may throw  
    UnsupportedOperationException

- An alternative design would have separate interfaces:

```
interface Collection { contains, containsAll, size, iterator, ... }
interface Expandable { add, addAll }
interface Shrinkable { remove, removeAll, difference, ... }
interface ModifiableCollection
    extends Collection, Expandable, Shrinkable { }
...
```

You'd soon have lots of interfaces. Perhaps that's why they didn't do it that way.)


## The List Interface

- Extends Collection
- Intended to represent *indexed sequences* (generalized arrays)
- Adds new methods to those of Collection:
  - Membership tests: indexOf, lastIndexOf.
  - Retrieval: get(*i*), listIterator(), sublist(*B*, *E*).
  - Modifiers: add and addAll with additional index to say *where* to add. Likewise for removal operations. set operation to go with get.
- Type ListIterator<Item> extends Iterator<Item>:
  - Adds previous and hasPrevious.
  - add, remove, and set allow one to iterate through a list, inserting, removing, or changing as you go.
  - **Important Question:** What advantage is there to saying List L rather than LinkedList L or ArrayList L?

## Views

**New Concept:** A *view* is an alternative presentation of (interface to) an existing object.

- For example, the sublist method is supposed to yield a "view of" part of an existing list:



- Example: after L.set(2, "bag"), value of SL.get(1) is "bag", and after SL.set(1, "bad"), value of L.get(2) is "bad".
- Example: after SL.clear(), L will contain only "at" and "cat".
- Small challenge: "How do they do that?!"

## Maps

- A Map is a kind of "modifiable function:"

```
package java.util;
public interface Map<Key,Value> {
    Value get (Object key);           // Value at KEY.
    Object put (Key key, Value value); // Set get(KEY) -> VALUE
    ...
}
-----
Map<String,String> f = new TreeMap<String,String> ();
f.put ("Paul", "George"); f.put ("George", "Martin");
f.put ("Dana", "John");
// Now f.get ("Paul").equals ("George")
//     f.get ("Dana").equals ("John")
//     f.get ("Tom") == null
```

## Map Views

```
public interface Map<Key,Value> { // Continuation
    /* VIEWS */
    /** The set of all keys. */
    Set<Key> keySet ();
    /** The multiset of all values */
    Collection<Value> values ();
    /** The set of all (key, value) pairs */
    Set<Map.Entry<Key,Value>> entrySet ();
}
```

Using example from previous slide:

```
for (Iterator<String> i = f.keySet ().iterator (); i.hasNext ();)
    i.next () ==> Dana, George, Paul
// or, just:
for (String name : f.keySet ())
    name ==> Dana, George, Paul

for (String parent : f.values ())
    parent ==> John, Martin, George
for (Map.Entry<String,String> pair : f.entrySet ())
    pair ==> (Dana,John), (George,Martin), (Paul,George)
f.keySet ().remove ("Dana"); // Now f.get("Dana") == null
```