

CS61B Lecture #18

Today:

- Overview of standard Java Collections classes.
 - Iterators, ListIterators
 - Containers and maps in the abstract
 - Views


Readings for Today: *Data Structures, Chapter 2.*

Readings for next Topic: *Data Structures, Chapter 3.*

Data Types in the Abstract

- Most of the time, should *not* worry about implementation of data structures, search, etc.
- What they do for us—their specification—is important.
- Java has several standard types (in `java.util`) to represent collections of objects
 - Six interfaces:
 - * Collection: General collections of items.
 - * List: Indexed sequences with duplication
 - * Set, SortedSet: Collections without duplication
 - * Map, SortedMap: Dictionaries ($\text{key} \mapsto \text{value}$)
 - Concrete classes that provide actual instances: `LinkedList`, `ArrayList`, `HashSet`, `TreeSet`.
 - To make change easier, purists would use the concrete types only for new, interfaces for parameter types, local variables.

Collection Structures in java.util



The Collection Interface

- Collection interface. Main functions promised:
 - Membership tests: contains (\in), containsAll (\subseteq)
 - Other queries: size, isEmpty
 - Retrieval: iterator, toArray
 - *Optional* modifiers: add, addAll, clear, remove, removeAll (*set difference*), retainAll (*intersect*)
- Design point (a side trip): Optional operations may throw
 UnsupportedOperationException
- An alternative design would have separate interfaces:

```
interface Collection { contains, containsAll, size, iterator, ... }  
interface Expandable { add, addAll }  
interface Shrinkable { remove, removeAll, difference, ... }  
interface ModifiableCollection  
    extends Collection, Expandable, Shrinkable { }  
...
```

You'd soon have lots of interfaces. Perhaps that's why they didn't do it that way.)


The List Interface

- Extends Collection
- Intended to represent *indexed sequences* (generalized arrays)
- Adds new methods to those of Collection:
 - Membership tests: `indexOf`, `lastIndexOf`.
 - Retrieval: `get(i)`, `listIterator()`, `sublist(B, E)`.
 - Modifiers: add and `addAll` with additional index to say *where* to add. Likewise for removal operations. set operation to go with get.
- Type `ListIterator<Item>` extends `Iterator<Item>`:
 - Adds `previous` and `hasPrevious`.
 - `add`, `remove`, and `set` allow one to iterate through a list, inserting, removing, or changing as you go.
 - **Important Question:** What advantage is there to saying List L rather than `LinkedList L` or `ArrayList L`?

Views

New Concept: A view is an alternative presentation of (interface to) an existing object.

- For example, the sublist method is supposed to yield a "view of" part of an existing list:



```
List<String> L = new ArrayList<String>();  
L.add ("at"); L.add("ax"); ...  
List<String> SL = L.sublist (1,4);
```

- Example: after `L.set(2, "bag")`, value of `SL.get(1)` is "bag", and after `SL.set(1,"bad")`, value of `L.get(2)` is "bad".
- Example: after `SL.clear()`, L will contain only "at" and "cat".
- Small challenge: "How do they do that?!"

Maps

- A Map is a kind of "modifiable function:"

```
package java.util;
public interface Map<Key,Value> {
    Value get (Object key);                      // Value at KEY.
    Object put (Key key, Value value);           // Set get(KEY) -> VALUE
    ...
}
```

```
Map<String,String> f = new TreeMap<String,String> ();
f.put ("Paul", "George"); f.put ("George", "Martin");
f.put ("Dana", "John");
// Now f.get ("Paul").equals ("George")
//       f.get ("Dana").equals ("John")
//       f.get ("Tom") == null
```

Map Views

```
public interface Map<Key,Value> { // Continuation
    /* VIEWS */
    /** The set of all keys. */
    Set<Key> keySet ();
    /** The multiset of all values */
    Collection<Value> values ();
    /** The set of all (key, value) pairs */
    Set<Map.Entry<Key,Value>> entrySet ();
}
```

Using example from previous slide:

```
for (Iterator<String> i = f.keySet ().iterator (); i.hasNext ())
    i.next () ==> Dana, George, Paul
// or, just:
for (String name : f.keySet ())
    name ==> Dana, George, Paul

for (String parent : f.values ())
    parent ==> John, Martin, George
for (Map.Entry<String,String> pair : f.entrySet ())
    pair ==> (Dana,John), (George,Martin), (Paul,George)
f.keySet ().remove ("Dana"); // Now f.get("Dana") == null
```