

CS61B Lecture #2

- Please make sure you have obtained an account and used our "Account Administration" page to register and create keys by the end of the first lab.
- Reminder: no class on Monday.
- Pick up readers at Vick Copy (there are two), unless you think you can do everything on-line.
- No, there are no other texts, no matter what anything says.
- I will deal with waitlisted students soon. Expect to get in.

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 1

Today's Words of Wisdom

RTFM

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 2

Prime Numbers

Problem: want java PrintPrimes0 U to print prime numbers through U .

You type: java primes 101

It types: 2 3 5 7 11 13 17 19 23 29
31 37 41 43 47 53 59 61 67 71
73 79 83 89 97 101

Definition: A *prime number* is an integer greater than 1 that has no divisors smaller than itself other than 1.

Useful Facts:

- If $k \leq \sqrt{N}$, then $N/k \geq \sqrt{N}$, for $N, k > 0$.
- k divides N iff N/k divides N .

So: Try all potential divisors up to and including the square root.

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 3

Plan

```
class primes {
    /** Print all primes up to ARGS[0] (interpreted as an
     * integer), 10 to a line. */
    public static void main (String[] args) {
        printPrimes (Integer.parseInt (args[0]));
    }

    /** Print all primes up to and including LIMIT, 10 to
     * a line. */
    private static void printPrimes (int limit) {
        /*{ For every integer, x, between 2 and LIMIT, print it if
         isPrime (x), 10 to a line. }*/
    }

    /** True iff X is prime */
    private static boolean isPrime (int x) {
        return /*( X is prime )*/;
    }
}
```

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 4

Testing for Primes

```
private static boolean isPrime (int x) {
    if (x <= 1)
        return false;
    else
        return ! isDivisible (x, 2); // "!" means "not"
}

/** True iff X is divisible by any positive number >=K and < X,
 * given K > 1. */
private static boolean isDivisible (int x, int k) {
    if (k >= x) // a "guard"
        return false;
    else if (x % k == 0) // "%" means "remainder"
        return true;
    else // if (k < x && x % k != 0)
        return isDivisible (x, k+1);
}
```

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 5

Thinking Recursively

Understand and check `isDivisible(13,2)` by *tracing one level*.

```
/** True iff X is divisible by
 * some number >=K and < X,
 * given K > 1. */
boolean isDivisible (int x, int k) {
    if (k >= x)
        return false;
    else if (x % k == 0)
        return true;
    else
        return isDivisible (x, k+1);
}
```

Lesson: Comments aid understanding. Make them count!

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 6

- Call assigns $x=13, k=2$
- Body has form 'if ($k \geq x$) S_1 else S_2 '.
- Since $2 < 13$, we evaluate the first else.
- Check if $13 \bmod 2 = 0$; it's not.
- Left with `isDivisible(13,3)`.
- Rather than tracing it, instead use the *comment*:
- Since 13 is *not* divisible by any integer in the range 3..12 (and $3 > 1$), `isDivisible(13,3)` must be *false*, and we're done!
- Sounds like that last step begs the question. Why doesn't it?

Iteration

- `isDivisible` is *tail recursive*, and so creates an *iterative process*.
- Traditional "Algol family" production languages have special syntax for iteration. Four equivalent versions of `isDivisible`:

```
if (k >= x)                while (k < x) { // ! (k >= x)
    return false;          if (x % k == 0)
else if (x % k == 0)      return true;
    return true;          k = k+1;
else                       // or k += 1, or k++ (yuch).
    return isDivisible (x, k+1);}
                           return false;
```

```
int k1 = k;                for (int k1 = k; k1 < x; k1 += 1) {
while (k1 < x) {          if (x % k1 == 0)
    if (x % k1 == 0)      return true;
        return true;    }
    k1 += 1;              return false;
}
return false;
```

Last modified: Wed Sep 3 01:04:24 2008

CS61B: Lecture #2 7