

CS152
Computer Architecture and Engineering

Memory Consistency and
Cache Coherence
Problem Set #5

Assigned November 9

Due November 17

<http://inst.eecs.berkeley.edu/~cs152/fa16>

The problem sets are intended to help you learn the material, and we encourage you to collaborate with other students and to ask questions in discussion sections and office hours to understand the problems. However, each student must turn in his own solution to the problems.

The problem sets also provide essential background material for the quizzes. The problem sets will be graded primarily on an effort basis, but if you do not work through the problem sets you are unlikely to succeed at the quizzes! Homework assignments are due at the beginning of class on the due date. Late homework will not be accepted.

Problem P5.1: Sequential Consistency

For this problem we will be using the following sequences of instructions. These are small programs, each executed on a different processor, each with its own cache and register set. In the following **R** is a register and **X** is a memory location. Each instruction has been named (e.g., B3) to make it easy to write answers.

Assume data in location X is initially 0.

Processor A	Processor B	Processor C
A1: ST X, 1	B1: R := LD X	C1: ST X, 6
A2: R := LD X	B2: R := ADD R, 1	C2: R := LD X
A3: R := ADD R, R	B3: ST X, R	C3: R := ADD R, R
A4: ST X, R	B4: R := LD X	C4: ST X, R
	B5: R := ADD R, R	
	B6: ST X, R	

For each of the questions below, please circle the answer and provide a short explanation assuming the program is executing under the SC model. **No points will be given for just circling an answer!**

Problem P5.1.A

Can X hold value of 4 after all three threads have completed? Please explain briefly.

Yes / No

Problem P5.1.B

Can X hold value of 5 after all three threads have completed?

Yes / No

Problem P5.1.C

Can X hold value of 6 after all three threads have completed?

Yes / No

Problem P5.1.D

For this particular program, can a processor that reorders instructions but follows local dependencies produce an answer that cannot be produced under the SC model?

Yes / No

Problem P5.2: Synchronization Primitives

One of the common instruction sequences used for synchronizing several processors are the LOAD RESERVE/STORE CONDITIONAL pair (from now on referred to as LdR/StC pair). The LdR instruction reads a value from the specified address and sets a local reservation for the address. The StC attempts to write to the specified address provided the local reservation for the address is still held. If the reservation has been cleared the StC fails and informs the CPU.

Problem P5.2.A

Describe under what events the local reservation for an address is cleared.

Problem P5.2.B

Is it possible to implement LdR/StC pair in such a way that the memory bus is not affected, i.e., unaware of the addition of these new instructions? Explain

Problem P5.2.C

Give two reasons why the LdR/StC pair of instructions is preferable over atomic read-test-modify instructions such as the TEST&SET instruction.

Problem P5.2.D

LdR/StC pair of instructions were conceived in the context of snoopy busses. Do these instructions make sense in our directory-based system in Handout #6? Do they still offer an advantage over atomic read-test-modify instructions in a directory-based system? Please explain.

Problem P5.3: Relaxed Memory Models

The following code implements a *seqlock*, which is a reader-writer lock that supports a single writer and multiple readers. The writer never has to wait to update the data protected by the lock, but readers may have to wait if the writer is busy. We use a seqlock to protect a variable that holds the current time. The lock is necessary because the variable is 64 bits and thus cannot be read or written atomically on a 32-bit system.

The seqlock is implemented using a sequence number, *seqno*, which is initially zero. The writer begins by incrementing *seqno*. It then writes the new time value, which is split into the 32-bit values *time_lo* and *time_hi*. Finally, it increments *seqno* again. Thus, if and only if *seqno* is odd, the writer is currently updating the counter.

The reader begins by waiting until *seqno* is even. It then reads *time_lo* and *time_hi*. Finally, it reads *seqno* again. If *seqno* didn't change from the first read, then the read was successful; otherwise, the read is retried.

This code is correct on a sequentially consistent system, but on a system with a fully relaxed memory model it may not be. Insert the minimum number of memory fences to make the code correct on a system with a relaxed memory model. To insert a fence, write the needed fence (Membar_{LL}, Membar_{LS}, Membar_{SL}, Membar_{SS}) in between the lines of code below.

Writer	Reader
LOAD R _{seqno} , (seqno)	Loop: LOAD R _{seqno_before} ,
ADD R _{seqno} , R _{seqno} , 1	(seqno)
STORE (seqno), R _{seqno}	IF (R _{seqno_before} & 1)
STORE (time_lo), R _{time_lo}	goto Loop
STORE (time_hi), R _{time_hi}	LOAD R _{time_lo} , (time_lo)
ADD R _{seqno} , R _{seqno} , 1	LOAD R _{time_hi} , (time_hi)
STORE (seqno), R _{seqno}	LOAD R _{seqno_after} , (seqno)
	IF (R _{seqno_before} != R _{seqno_after})
	goto Loop

Problem P5.4: Locking Performance

While analyzing some code, you find that a big performance bottleneck involves many threads trying to acquire a single lock.

Conceptually, the code is as follows:

```
int mutex = 0;

while( true )
{
    noncritical_code( );

    lock( &mutex );
    critical_code(
); unlock(
&mutex );
}
```

Assume for all questions that our processor is using a directory protocol, as described in Handout #6.

Test&Set Implementation

First, we will use the atomic instruction `test&set` to implement the `lock(mutex)` and `unlock(mutex)` functions.

In C, the instruction has the following function prototype:

```
int return_value = test&set(int* maddr);
```

Recall that `test&set` atomically reads the memory address `maddr` and writes a 1 to the location, returning the original value.

Using `test&set`, we arrive at the following first-draft implementation for the `lock()` and `unlock()` functions:

```
void inline lock(int* mutex_ptr)
{
    while(test&set(mutex_ptr) == 1);
}

void inline unlock(int* mutex_ptr)
{
    *mutex_ptr = 0;
}
```

Problem P5.4.A**Test&Set, The Initial Acquire**

Let us analyze the behavior of `Test&Set` while running 1,000 threads on a 1,000 cores.

Consider the following scenario: At the start of the program, the lock is invalid in all caches. Then, every thread executes `Test&Set` once. The first thread wins the lock, while the other threads will find that the lock is taken. How many invalidation messages must be sent when all 1,000 threads execute `Test&Set` once?

Invalidations _____

Problem P5.4.B**Test&Set, Spinning**

While the first thread is in the critical section (the “winning thread”), the remaining threads continue to execute `Test&Set`, attempting to acquire the lock. Each waiting thread is able to execute `Test&Set` five times before the winning thread frees the lock. How many invalidation messages must be sent while the winning thread was executing the critical section?

Invalidations _____

Problem P5.4.C

Test&Set, Freeing the Lock

How many invalidation messages must be sent when the winning thread frees the lock? Assume the critical section is very long, and all 999 other threads have been waiting to acquire the lock.

Invalidations _____

Test&Test&Set Implementation

Since our analysis from the previous parts show that a lot of invalidation messages must be sent while waiting for the lock to be freed, let us instead use the atomic instruction `test&set` to implement Test&Test&Set.

```
void inline lock(int* mutex_ptr)
{
    while( (*mutex_ptr == 1) || test&set(mutex_ptr) == 1);
}
```

```
void inline unlock(int* mutex_ptr)
{
    *mutex_ptr = 0;
}
```

(Note: the loop evaluation is short-circuited if the first part is true; thus, `test&set` is only executed if `(*mutex_ptr)` does not equal 1).

Problem P5.4.D

Test&Set&Set, The Initial Acquire

Let us analyze the behavior of Test&Test&Set while running 1,000 threads on a 1,000 cores.

Consider the following scenario: At the start of the program, the lock is invalid in all caches. Then every thread performs the first Test (reading `mutex_ptr`) once. After every thread has performed the first Test (which evaluates to *False*, because `mutex == 0`), each thread then executes the atomic Test&Set once. Naturally, only one thread wins the lock. How many invalidation messages must be sent in this scenario?

Problem P5.4.E

Invalidations _____

Test&Set&Set, Spinning

While the first thread is in the critical section, the remaining threads continue to execute Test&Test&Set. Each waiting thread is able to execute Test&Test&Set five times before the winning thread frees the lock. How many invalidation messages must be sent while the winning thread was executing the critical section?

Invalidations _____

Problem P5.4.F

Test&Set&Set, Freeing the Lock

How many invalidation messages must be sent when the winning thread frees the lock for the Test&Test&Set implementation? Assume the critical section is very long, and all 999 other threads have been waiting to acquire the lock.

Invalidations _____

Problem P5.5: Directory-based Cache Coherence Invalidate Protocols

In this problem we consider a cache-coherence protocol presented in Handout #6.

Problem P5.5.A

Protocol Understanding

Consider the situation in which memory sends a **FlushReq** message to a processor. This can only happen when the memory directory shows that the exclusive copy resides at that site. The memory processor intends to obtain the most up-to-date data and exclusive ownership, and then supply it to another site that has issued a **ExReq**. Table H12-1 row 21 specifies the PP behavior when the current cache state is C-pending (not C-exclusive) and a **FlushReq** is received.

Give a simple scenario that causes this situation.

Problem P5.5.B

Non-FIFO Network

FIFO message passing is a necessary assumption for the correctness of the protocol. Assume now that the network is non-FIFO. Give a simple scenario that shows how the protocol fails.

Problem P5.5.C

Replace

In the current scheme, when a cache wants to voluntarily invalidate a shared cache line, the PP informs the memory of this operation. Describe a simple scenario where there would be an error, if the line was “silently dropped.” Can you provide a simple fix for this problem in the protocol? Give such a fix if there is one, or explain why it wouldn’t be a simple fix.

Problem P5.6: Directory-based Cache Coherence Update Protocols

In Handout #6, we examined a cache-coherent distributed shared memory system. Ben wants to convert the directory-based invalidate cache coherence protocol from the handout into an update protocol. He proposes the following scheme.

Caches are write-through, not write allocate. When a processor wants to write to a memory location, it sends a **WriteReq** to the memory, along with the data word that it wants written. The memory processor updates the memory, and sends an **UpdateReq** with the new data to each of the sites caching the block, unless that site is the processor performing the store, in which case it sends a **WriteRep** containing the new data.

If the processor performing the store is caching the block being written, it must wait for the reply from the home site to arrive before storing the new value into its cache. If the processor performing the store is not caching the block being written, it can proceed after issuing the **WriteReq**.

Ben wants his protocol to perform well, and so he also proposes to implement silent drops. When a cache line needs to be evicted, it is silently evicted and the memory processor is not notified of this event.

Note that **WriteReq** and **UpdateReq** contain data at the word-granularity, and not at the block-granularity. Also note that in the proposed scheme, memory will always have the most up-to-date data and the state C-exclusive is no longer used.

As in the lecture, the interconnection network guarantees that message-passing is reliable, and free from deadlock, livelock, and starvation. Also as in the lecture, message-passing is FIFO.

Each home site keeps a FIFO queue of incoming requests, and processes these in the order received.

Problem P5.6.A

Sequential Consistency

Alyssa claims that Ben's protocol does not preserve sequential consistency because it allows two processors to observe stores in different orders. Describe a scenario in which this problem can occur.

Problem P5.6.B**State Transitions**

Noting that many commercial systems do not guarantee sequential consistency, Ben decides to implement his protocol anyway. Fill in the following state transition tables (Table P5.6-1 and Table P5.6-2) for the proposed scheme. (Note: the tables do not contain all the transitions for the protocol).

No.	Current State	Event Received	Next State	Action
1	C-nothing	Load	C-transient	ShReq(id, Home, a)
2	C-nothing	Store		
3	C-nothing	UpdateReq		
4	C-shared	Load	C-shared	processor reads cache
5	C-shared	Store		
6	C-shared	UpdateReq		
7	C-shared	(Silent drop)		Nothing
8	C-transient	ShRep		data → cache, processor reads cache
9	C-transient	WriteRep		
10	C-transient	UpdateReq		

Table P5.6-1: Cache State Transitions

No.	Current State	Message Received	Next State	Action
1	R(dir) & id N dir	ShReq	R(dir + {id})	ShRep(Home, id, a)
2	R(dir) & id N dir	WriteReq		
3	R(dir) & id N dir	ShReq		ShRep(Home, id, a)
4	R(dir) & id N dir	WriteReq		

Table P5.6-2: Home Directory State Transitions (N = “is not in”)

Problem P5.6.C**UpdateReq**

After running a system with this protocol for a long time, Ben finds that the network is flooded with UpdateReqs. Alyssa says this is a bug in his protocol. What is the problem and how can you fix it?

Problem P5.6.D**FIFO Assumption**

As in P5.3, FIFO message passing is a necessary assumption for the correctness of the protocol. If the network were non-FIFO, it becomes possible for a processor to never see the result of another processor's store. Describe a scenario in which this problem can occur.

Problem P5.7: Snoopy Cache Coherent Shared Memory

In this problem, we investigate the operation of the snoopy cache coherence protocol in Handout #7.

The following questions are to help you check your understanding of the coherence protocol.

- Explain the differences between **CR**, **CI**, and **CRI** in terms of their purpose, usage, and the actions that must be taken by memory and by the different caches involved.
- Explain why **WR** is not snooped on the bus.
- Explain the I/O coherence problem that **CWI** helps avoid.

Problem P5.7.A Where in the Memory System is the Current Value

In Table P5.7-1, P5.7-2, and P5.7-3, column 1 indicates the initial state of a certain address X in a cache. Column 2 indicates whether address X is currently cached in any other cache. (The “cached” information is known to the cache controller only immediately following a bus transaction. Thus, the action taken by the cache controller must be independent of this signal, but state transition could depend on this knowledge.) Column 3 enumerates all the available operations on address X, either issued by the CPU (read, write), snooped on the bus (**CR**, **CRI**, **CI**, etc), or initiated by the cache itself (replacement). Some state-operation combinations are impossible; you should mark them as such. (See the first table for examples). In columns 6, 7, and 8 (corresponding to this cache, other caches and memory, respectively), **check all possible locations where up-to-date copies of this data block could exist after the operation in column 3 has taken place** and ignore column 4 and 5 for now. Table P5.7-1 has been completed for you. Make sure the answers in this table make sense to you.

Problem P5.7.B MBus Cache Block State Transition Table

In this problem, **we ask you to fill out the state transitions in Column 4 and 5**. In column 5, fill in the resulting state after the operation in column 3 has taken place. In column 4, list the necessary MBus transactions that are issued by the cache as part of the transition. Remember, the protocol should be optimized such that data is supplied using **CCI** *whenever possible*, and only the cache that *owns* a line should issue **CCI**.

Problem P5.7.C**Adding atomic memory operations to MBus**

We have discussed the importance of atomic memory operations for processor synchronization. In this problem you will be looking at adding support for an atomic fetch-and-increment to the MBus protocol.

Imagine a dual processor machine with CPUs A and B. Explain the difficulty of CPU A performing fetch-and-increment(x) when the most recent copy of x is cleanExclusive in CPU B's cache. You may wish to illustrate the problem with a short sequence of events at processor A and B.

Fill in the rest of the table below as before, indicating state, next state, where the block in question may reside, and the CPU A and MBus transactions that would need to occur atomically to implement a fetch-and-increment on processor A.

State	other cached	ops	actions by this cache	next state	this cache	other caches	mem
Invalid	yes	read					
		write					

initial state	other cached	ops	actions by this cache	final state	this cache	other caches	mem
Invalid	no	none	none	I			⌀
		CPU read	CR	CE	⌀		⌀
		CPU write	CRI	OE	⌀		
		replace	none	<i>Impossible</i>			
		CR	none	I		⌀	⌀
		CRI	none	I		⌀	
		CI	none	<i>Impossible</i>			
		WR	none	<i>Impossible</i>			
		CWI	none	I			⌀
Invalid	yes	none	same as above	I		⌀	⌀
		CPU read		CS	⌀	⌀	⌀
		CPU write		OE	⌀		
		replace		<i>Impossible</i>			
		CR		I		⌀	⌀
		CRI		I		⌀	
		CI		I		⌀	
		WR		I		⌀	⌀
		CWI		I			⌀

initial state	other cached	ops	actions by this cache	final state	this cache	other caches	mem
cleanExclusive	no	none	none	CE			
		CPU read					
		CPU write					
		replace					
		CR		CS			
		CRI					
		CI					
		WR					
CWI							

Table P5.7-1

initial state	other cached	ops	actions by this cache	final state	this cache	other caches	mem
ownedExclusive	no	none	none	OE			
		CPU read					
		CPU write					
		replace					
		CR		OS			
		CRI					
		CI					
		WR					
CWI							

initial state	other cached	ops	actions by this cache	final state	this cache	other caches	mem
cleanShared	no	none	none	CS			
		CPU read					
		CPU write					
		replace					
		CR					
		CRI					
		CI					
		WR					
CWI							
cleanShared	yes	none	same as above				
		CPU read					
		CPU write					
		replace					
		CR					
		CRI					
		CI					
		WR					
CWI							

Table P5.7-2

initial state	other cached	ops	actions by this cache	final state	this cache	other mem caches	mem
ownedShared	no	none	none	OS			
		CPU read					
		CPU write					
		replace					
		CR					
		CRI					
		CI					
		WR					
		CWI					
ownedShared	yes	none	same as above				
		CPU read					
		CPU write					
		replace					
		CR					
		CRI					
		CI					
		WR					
		CWI					

Table P5.7-3