

CS 188: Artificial Intelligence

Fall 2007

Lecture 5: CSPs II

9/11/2007

Dan Klein – UC Berkeley


Many slides over the course adapted from either Stuart Russell or Andrew Moore

Today

- More CSPs
 - Applications
 - Tree Algorithms
 - Cutset Conditioning
- Local Search

Reminder: CSPs

- CSPs:
 - Variables
 - Domains
 - Constraints
 - Implicit (provide code to compute)
 - Explicit (provide a subset of the possible tuples)
- Unary Constraints
- Binary Constraints
- N-ary Constraints



Example: Boolean Satisfiability

- Given a Boolean expression, is it satisfiable?
- Very basic problem in computer science

$$p_1 \wedge (p_2 \rightarrow p_3) \wedge ((\neg p_1 \wedge \neg p_3) \rightarrow \neg p_2) \wedge (p_1 \vee p_3)$$

- Turns out you can always express in 3-CNF

$$(p_1) \wedge (\neg p_2 \vee p_3) \wedge (p_1 \vee p_3 \vee \neg p_2) \wedge (p_1 \vee p_2 \vee p_3)$$


- 3-SAT: find a satisfying truth assignment

Example: 3-SAT

- Variables: p_1, p_2, \dots, p_n
 - Domains: $\{\text{true}, \text{false}\}$
 - Constraints: $p_i \vee p_j \vee p_k$
 $\neg p_{i'} \vee p_{j'} \vee p_{k'}$
 \vdots
 $p_{i''} \vee \neg p_{j''} \vee \neg p_{k''}$
- Implicitly conjoined
(all clauses must be satisfied)*

CSPs: Queries

- Types of queries:
 - Legal assignment (last class)
 - All assignments
 - Possible values of some query variable(s) given some evidence (partial assignments)



Example: N-Queens


- Formulation 3:

- Variables: Q_k

- Domains: $\{1, 2, 3, \dots, N\}$

- Constraints:

$$\forall i, j \quad (i; Q_i, j; Q_j) \in \{(1; 1, 2; 3), (1; 1, 2; 4), \dots\}$$

$$\forall i, j \quad \text{non-threatening}(i; Q_i, j; Q_j)$$


Reminder: Consistency

- Basic solution: DFS / backtracking



- Add a new assignment
- Check for violations

- Forward checking:

- Pre-filter unassigned domains after every assignment
- Only remove values which immediately conflict with current assignments

- Arc consistency

- We only defined it for binary CSPs
- Check for impossible values on all pairs of variables, prune them
- Run after each assignment, but before recursing
- A pre-filter, not search!



Arc Consistency

```

function AC-3(csp) returns the CSP, possibly with reduced domains
inputs: csp, a binary CSP with variables  $\{X_1, X_2, \dots, X_n\}$ 
local variables: queue, a queue of arcs, initially all the arcs in csp

while queue is not empty do
  ( $X_i, X_j$ )  $\leftarrow$  REMOVE-FIRST(queue)
  if REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) then
    for each  $X_k$  in NEIGHBORS[ $X_i$ ] do
      add ( $X_k, X_i$ ) to queue

```

```



function REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) returns true iff succeeds
  removed  $\leftarrow$  false
  for each  $x$  in DOMAIN[ $X_i$ ] do
    if no value  $y$  in DOMAIN[ $X_j$ ] allows ( $x, y$ ) to satisfy the constraint  $X_i \leftrightarrow X_j$ 
    then delete  $x$  from DOMAIN[ $X_i$ ]; removed  $\leftarrow$  true
  return removed

```

▪ [DEMO]

Limitations of Arc Consistency


- After running arc consistency:
 - Can have one solution left
 - Can have multiple solutions left
 - Can have no solutions left (and not know it)



What went wrong here?

K-Consistency

- Increasing degrees of consistency
 - 1-Consistency (Node Consistency): Each single node's domain has a value which meets that node's unary constraints
 - 2-Consistency (Arc Consistency): For each pair of nodes, any consistent assignment to one can be extended to the other
 - K-Consistency: For each k nodes, any consistent assignment to k-1 can be extended to the kth node.
- Higher k more expensive to compute
- (You need to know the k=2 algorithm)




Strong K-Consistency


- Strong k-consistency: also k-1, k-2, ... 1 consistent
- Claim: strong n-consistency means we can solve without backtracking!
- Why?
 - Choose any assignment to any variable
 - Choose a new variable
 - By 2-consistency, there is a choice consistent with the first
 - Choose a new variable
 - By 3-consistency, there is a choice consistent with the first 2
 - ...
- Lots of middle ground between arc consistency and n-consistency! (e.g. path consistency)

Problem Structure

- Tasmania and mainland are independent subproblems
- Identifiable as connected components of constraint graph
- Suppose each subproblem has c variables out of n total
 - Worst-case solution cost is $O((n/c)(d^c))$, linear in n
 - E.g., $n = 80$, $d = 2$, $c = 20$
 - $2^{80} = 4$ billion years at 10 million nodes/sec
 - $(4)(2^{20}) = 0.4$ seconds at 10 million nodes/sec





Tree-Structured CSPs



- Theorem: if the constraint graph has no loops, the CSP can be solved in $O(n d^2)$ time
 - Compare to general CSPs, where worst-case time is $O(d^n)$
- This property also applies to logical and probabilistic reasoning: an important example of the relation between syntactic restrictions and the complexity of reasoning.

Tree-Structured CSPs

- Choose a variable as root, order variables from root to leaves such that every node's parent precedes it in the ordering



- For $i = n : 2$, apply $\text{RemoveInconsistent}(\text{Parent}(X_i), X_i)$
- For $i = 1 : n$, assign X_i consistently with $\text{Parent}(X_i)$
- Runtime: $O(n d^2)$ (why?)


Tree-Structured CSPs

- Why does this work?
- Claim: After each node is processed leftward, all nodes to the right can be assigned in any way consistent with their parent.
- Proof: Induction on position



- Why doesn't this algorithm work with loops?
- Note: we'll see this basic idea again with Bayes' nets (and call it message passing)



Nearly Tree-Structured CSPs



- Conditioning: instantiate a variable, prune its neighbors' domains
- Cutset conditioning: instantiate (in all ways) a set of variables such that the remaining constraint graph is a tree
- Cutset size c gives runtime $O(d^c (n-c) d^2)$, very fast for small c

Types of Problems


- **Planning problems:**
 - We want a path to a solution (examples?)
 - Usually want an optimal path
 - *Incremental formulations*
- **Identification problems:**
 - We actually just want to know what the goal is (examples?)
 - Usually want an optimal goal
 - *Complete-state formulations*
 - Iterative improvement algorithms



Iterative Algorithms for CSPs

- Hill-climbing, simulated annealing typically work with “complete” states, i.e., all variables assigned
- To apply to CSPs:
 - Allow states with unsatisfied constraints
 - Operators *reassign* variable values
- Variable selection: randomly select any conflicted variable
- Value selection by min-conflicts heuristic:
 - Choose value that violates the fewest constraints
 - I.e., hillclimb with $h(n)$ = total number of violated constraints

Example: 4-Queens




- States: 4 queens in 4 columns ($4^4 = 256$ states)
- Operators: move queen in column
- Goal test: no attacks
- Evaluation: $h(n)$ = number of attacks

Performance of Min-Conflicts

- Given random initial state, can solve n-queens in almost constant time for arbitrary n with high probability (e.g., n = 10,000,000)
- The same appears to be true for any randomly-generated CSP *except* in a narrow range of the ratio

$$R = \frac{\text{number of constraints}}{\text{number of variables}}$$



CSP Summary

- CSPs are a special kind of search problem:
 - States defined by values of a fixed set of variables
 - Goal test defined by constraints on variable values
- Backtracking = depth-first search with one legal variable assigned per node
- Variable ordering and value selection heuristics help significantly
- Forward checking prevents assignments that guarantee later failure
- Constraint propagation (e.g., arc consistency) does additional work to constrain values and detect inconsistencies
- The constraint graph representation allows analysis of problem structure
- Tree-structured CSPs can be solved in linear time
- Iterative min-conflicts is usually effective in practice


Local Search Methods

- Queue-based algorithms keep fallback options (backtracking)
- Local search: improve what you have until you can't make it better
- Generally much more efficient (but incomplete)

Hill Climbing

- Simple, general idea:
 - Start wherever
 - Always choose the best neighbor
 - If no neighbors have better scores than current, quit
- Why can this be a terrible idea?
 - Complete?
 - Optimal?
- What's good about it?

Hill Climbing Diagram



- Random restarts?
- Random sideways steps?

Simulated Annealing

- Idea: Escape local maxima by allowing downhill moves
 - But make them rarer as time goes on

function SIMULATED-ANNEALING(*problem*, *schedule*) **returns** a solution state

inputs: *problem*, a problem

schedule, a mapping from time to "temperature"

local variables: *current*, a node

next, a node

T, a "temperature" controlling prob. of downward steps

current ← MAKE-NODE(INITIAL-STATE[*problem*])

for *t* ← 1 **to** ∞ **do**

T ← *schedule*[*t*]

if *T* = 0 **then return** *current*

next ← a randomly selected successor of *current*

ΔE ← VALUE[*next*] − VALUE[*current*]

if $\Delta E > 0$ **then** *current* ← *next*


else *current* ← *next* only with probability $e^{-\Delta E/T}$

Simulated Annealing


- Theoretical guarantee:
 - Stationary distribution: $p(x) \propto e^{-\frac{E(x)}{kT}}$
 - If T decreased slowly enough, will converge to optimal state!
- Is this an interesting guarantee?
- Sounds like magic, but reality is reality:
 - The more downhill steps you need to escape, the less likely you are to ever make them all in a row
 - People think hard about *ridge operators* which let you jump around the space in better ways

Beam Search

- Like greedy hillclimbing search, but keep K states at all times:




Greedy Search



Beam Search


- Variables: beam size, encourage diversity?
- The best choice in MANY practical settings
- Complete? Optimal?
- Why do we still need optimal methods?

Genetic Algorithms



- Genetic algorithms use a natural selection metaphor
- Like beam search (selection), but also have pairwise crossover operators, with optional mutation
- Probably the most misunderstood, misapplied (and even maligned) technique around!


Example: N-Queens



- Why does crossover make sense here?
- When wouldn't it make sense?
- What would mutation be?
- What would a good fitness function be?

Continuous Problems

- Placing airports in Romania
 - States: $(x_1, y_1, x_2, y_2, x_3, y_3)$
 - Cost: sum of squared distances to closest city



Gradient Methods

- How to deal with continuous (therefore infinite) state spaces?
- Discretization: bucket ranges of values
 - E.g. force integral coordinates
- Continuous optimization
 - E.g. gradient ascent

$$\nabla f = \left(\frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$
$$x \leftarrow x + \alpha \nabla f(x)$$




Image from vias.org