

## CS61B Lecture #12: Integers

### Today:

- Integer Types

**Readings for Today:** *Blue Reader*, Chapter 4.

**Readings for Upcoming Topics:** *Blue Reader*, Chapter 5, *Yellow Reader*, Chapter 1.

**Reminder:** Have you started Project #1 yet?

Last modified: Mon Sep 27 12:09:51 2004

CS61B: Lecture #12 1

## Integer Types and Literals

Type	Bits	Signed?	Literals
byte	8	Yes	
short	16	Yes	
char	16	No	'a' // (char) 97 '\n' // newline ((char) 10) '\t' // tab ((char) 8) '\\' // backslash 'A', '\101', '\u0041' // == (char) 65
int	32	Yes	123 0100 // Octal for 64 0x3f, 0xffffffff // Hexadecimal 63, -1 (!)
long	64	Yes	123L, 01000L, 0x3fL 1234567891011L

- " $N$  bits" means that there are  $2^N$  integers in the domain of the type.
- If signed, range of values is  $-2^{N-1} \dots 2^{N-1} - 1$ .
- If unsigned, only non-negative numbers, and range is  $0 \dots 2^N - 1$ .
- Negative numerals are just negated (positive) literals.
- Use casting for **byte** and **short**: (byte) 12, (short) 2000.

Last modified: Mon Sep 27 12:09:51 2004

CS61B: Lecture #12 2

## Modular Arithmetic

- Problem:** How do we handle overflow, such as occurs in  $10000 * 10000 * 10000$ ?
- Some languages throw an exception (Ada), some give undefined results (C, C++)
- Java defines the result of any arithmetic operation or conversion on integer types to "wrap around"—*modular arithmetic*.
- That is, the "next number" after the largest in an integer type is the smallest (like "clock arithmetic").
- E.g., (byte) 128 == (byte) (127+1) == (byte) -128
- In general,
  - If the result of some arithmetic subexpression is supposed to have type  $T$ , an  $n$ -bit integer type,
  - then we compute the real (mathematical) value,  $x$ ,
  - and yield a number,  $x'$ , that is in the range of  $T$ , and that is equivalent to  $x$  modulo  $2^n$ .
  - (That means that  $x - x'$  is a multiple of  $2^n$ .)

Last modified: Mon Sep 27 12:09:51 2004

CS61B: Lecture #12 3

## Modular Arithmetic II

- (byte) (64\*8) yields 0, since  $512 - 0 = 2 \cdot 2^8$ .
- (byte) (64\*2) and (byte) (127+1) yield -128, since  $128 - (-128) = 1 \cdot 2^8$ .
- (byte) (345\*6) yields 22, since  $2070 - 22 = 8 \cdot 2^8$ .
- (byte) (-30\*13) yields 122, since  $-390 - 122 = -2 \cdot 2^8$ .
- (char) (-1) yields  $2^{16} - 1$ , since  $-1 - (2^{16} - 1) = 2^{16}$ .
- Why this definition? Quite natural for a machine that uses binary (base 2) arithmetic:

Type char	Type byte
	0 = 00000000 <sub>2</sub>
0 = 0000000000000000 <sub>2</sub>	1 = 00000001 <sub>2</sub>
$2^{16} - 1 = 1111111111111111_2$	127 = 01111111 <sub>2</sub>
	-128 = 10000000 <sub>2</sub>
	-1 = 11111111 <sub>2</sub>

- Terminology:** rightmost (units) bit is *bit 0*, 2s bit is *bit 1*. Hence, changing bit  $n$  modifies value by  $2^n$ .

Last modified: Mon Sep 27 12:09:51 2004

CS61B: Lecture #12 4

## Negative numbers

- Why this representation for -1?

$$\begin{array}{r|l} 1 & 00000001_2 \\ + -1 & 11111111_2 \\ \hline = 0 & 1|00000000_2 \end{array}$$

Only 8 bits in a byte, so bit 8 falls off, leaving 0.

- The truncated bit is in the  $2^8$  place, so throwing it away gives an equal number modulo  $2^8$ . All bits to the left of it are likewise divisible by  $2^8$ .
- On unsigned types (**char**), arithmetic is the same, but we choose to represent only non-negative numbers modulo  $2^{16}$ :

$$\begin{array}{r|l} 1 & 0000000000000001_2 \\ + 2^{16} - 1 & 1111111111111111_2 \\ \hline = 2^{16} + 0 & 1|0000000000000000_2 \end{array}$$

## Conversion

- In general Java will silently convert from one type to another if this makes sense and no information is lost from value.
- Otherwise, cast explicitly, as in (byte) x.
- Hence, given

```
byte aByte; char aChar; short aShort; int anInt; long aLong;
```

```
// OK:
aShort = aByte; anInt = aByte; anInt = aShort; anInt = aChar;
aLong = anInt;
```

```
// Not OK, might lose information:
anInt = aLong; aByte = anInt; aChar = anInt; aShort = anInt;
aShort = aChar; aChar = aShort; aChar = aByte;
```

```
// OK by special dispensation:
aByte = 13; // 13 is compile-time constant
aByte = 12+100 // 112 is compile-time constant
```

## Promotion

- Arithmetic operations (+, \*, ...) *promote* operands as needed.
- Promotion is just implicit conversion.
- For integer operations,
  - if any operand is **long**, promote both to **long**.
  - otherwise promote both to **int**.
- So,

```
aByte + 3 == (int) aByte + 3 // Type int
aLong + 3 == aLong + (long) 3 // Type long
'A' + 2 == (int) 'A' + 2 // Type int
aByte = aByte + 1 // ILLEGAL (why?)
```

- But fortunately,

```
aByte += 1; // Defined as aByte = (byte) (aByte+1)
```

- Common example:

```
// Assume aChar is an upper-case letter
char lowerCaseChar = (char) ('a' + aChar - 'A'); // why cast?
```

## Bit twiddling

- Java (and C, C++) allow for handling integer types as sequences of bits. No "conversion to bits" needed: they already are.
- Operations and their uses:

Mask	Set	Flip	Flip all
00101100	00101100	00101100	
& 10100111	10100111	^ 10100111	~ 10100111
00100100	10101111	10001011	01011000

- Shifting:

Left	Arithmetic Right	Logical Right
10101101 << 3	10101101 >> 3	10101100 >>> 3
01101000	11110101	00010101

- What is:
 

(-1) >>> 29?	
x << n?	
x >> n?	
(x >>> 3) & ((1<<5)-1)?	