

CALCULATOR 10

COMPUTER SCIENCE 61A

November 6th, 2013

We are beginning to dive into the realm of interpreting computer programs - that is, writing programs that understand programs. In order to do so, we'll have to examine programming languages in-depth. The **Calculator** language, a subset of Scheme, will be the first of these examples.

In today's discussion, we'll be looking at implementing Calculator using regular Python. We'll also take a look at **Exceptions**, a mechanism for handling unexpected execution - quite common when handling user input.

1 Calculator

For now, our Calculator language will be a Scheme-syntax language that can handle the four basic arithmetic operations. These operations can be nested and can take varying numbers of arguments. Here's a couple examples of Calculator in action:

```
> (+ 2 2)
4
```

```
> (- 5)
-5
```

```
> (* (+ 1 2) (+ 2 3))
15
```

Our goal now is to write an interpreter for this Calculator language. The job of an interpreter is, given an expression, evaluate its meaning. So let's talk about expressions.

1.1 Representing Expressions

There are two kinds of expressions. A **call expression** is a Scheme list - the first element is the operator, and each subsequent element is an operand. A **primitive expression** is an operator symbol or number. When we type a line at the Calculator prompt and hit enter, we've just sent an expression to the interpreter.

To represent Scheme lists in Python, we'll be using `Pair` objects. This is very similar to the `Rlists` we've been working with. The class definition is below:

```
class nil(object):
    """The empty list"""

    def __len__(self):
        return 0

    def map(self, fn):
        return self

nil = nil() #nil now refers to a single instance of nil class

class Pair(object):

    def __init__(self, first, second=nil):
        self.first = first
        self.second = second

    def __len__(self):
        n, second = 1, self.second
        while isinstance(second, Pair):
            n += 1
            second = second.second
        if second is not nil:
            raise TypeError("length attempted on improper list")
        return n

    def __getitem__(self, k):
        if k < 0:
            raise IndexError("negative index into list")
        j, y = 0, self
        while j < k:
            if y.second is nil:
```

```

        raise IndexError("list index out of bounds")
    elif not isinstance(y.second, Pair):
        raise TypeError("ill-formed list")
    j, y = j + 1, y.second
return y.first

def map(self, fn):
    """Returns a Scheme list after mapping Python function
    fn over self."""
    mapped = fn(self.first)
    if self.second is nil or isinstance(self.second, Pair):
        return Pair(mapped, self.second.map(fn))
    else:
        raise TypeError("ill-formed list")

def to_py_list(self):
    """Returns a Python list containing the elements of this
    Scheme list."""
    y, result = self, [ ]
    while y is not nil:
        result += [y.first]
        if not isinstance(y.second, Pair) or y.second is not nil:
            raise TypeError("ill-formed list")
        y = y.second
    return result

```

1.2 Questions

1. Translate the following Python representation of Calculator expressions into the proper Scheme-syntax:

```
>>> Pair('+', Pair(1, Pair(2, Pair(3, Pair(4, nil))))))
```

```
>>> Pair('+', Pair('1', Pair(Pair('*', Pair(2, Pair(3, nil))), nil)))
```

2. Translate the following Calculator expressions into calls to the `Pair` constructor.

```
> (+ 1 2 (- 3 4))
```

```
> (+ 1 (* 2 3) 4)
```

1.3 Evaluation

So what is evaluation? Evaluation discovers the form of an expression and executes a corresponding evaluation rule.

Primitive expressions are evaluated directly. Call expressions are evaluated recursively:

- (1) Evaluate each operand expression,
- (2) Collect their values as a list of arguments, and
- (3) **Apply** the named operator to the argument list.

Here's `calc_eval`:

```
def calc_eval(exp):  
    if not isinstance(exp, Pair): #expression is primitive  
        return exp  
    else:  
        operator, operands = exp.first, exp.second  
        args = operands.map(calc_eval).to_py_list()  
        return calc_apply(operator, args)
```

As you can see, all we've done is follow the rules of evaluation outlined above. If the expression is primitive (i.e. not a Scheme list), simply return it. Otherwise, evaluate the operands and apply the operator to the evaluated operands.

How do we apply the operator? We'll use `calc_apply`, with dispatching on the operator name:

```
def calc_apply(operator, args):  
    if operator == '+':  
        return sum(args)  
    elif operator == '-':  
        if len(args) == 1:  
            return -args[0]  
        else:  
            return sum(args[0], [-args for args in args[1:]])  
    elif operator == '*':  
        return reduce(mul, args, 1)
```

Depending on what the operator is, we can match it to a corresponding Python call. Each conditional clause above handles the application of one operator.

Something very important to keep in mind: `calc_eval` deals with **expressions**, `calc_apply` deals with **values**.

1.4 Questions

1. Suppose we typed each of the following expressions into the Calculator interpreter. How many calls to `calc_eval` would they each generate? How many calls to `calc_apply`?
> `(+ 2 4 6 8)`

> `(+ 2 (* 4 (- 6 8)))`
2. The `-` operator will fail if given no arguments. Add error handling to raise an exception when this situation is encountered (the type of exception is unimportant).
3. We also want to be able to perform division, as in `(/ 4 2)`. Supplement the existing code to handle this. If division by 0 is attempted, or if there are less than 2 arguments supplied, you should raise an exception (the type of exception is unimportant).
4. Alyssa P. Hacker and Ben Bitdiddle are also tasked with implementing the `and` operator, as in `(and (= 1 2) (< 3 4))`. Ben says this is easy: they just have to follow the same process as in implementing `*` and `/`. Alyssa is not so sure. Who's right?

5. Now that you've had a chance to think about it, you decide to try implementing it yourself. You may assume the conditional operators (e.g. `<`, `>`, `=`, etc) have already been implemented for you.

1.5 Bonus Questions

6. implement the `expt` operator such that the following works:

```
> (expt 2 3)
8
> (expt 3 4)
81
```

7. Implement `quote`. A `quote` expression simply returns its argument without evaluating it.

```
> (quote (2 (3 4) 5))
(2 (3 4) 5)
> (quote (+ 3 4))
(+ 3 4)
```

8. Implement the list operator. A list expression evaluates all its arguments and returns a list of their values.

```
> (list (+ 3 4) 5 (* 2 3))  
(7 5 6)  
> (list (+ 1 2) (quote (3 4)) 5)  
(3 (3 4) 5)
```

9. Now that we can create scheme-style lists in calculator, let's modify the + operator so that it can add lists together elementwise. You can assume that the lists are the same length and contain only numbers.

```
> (+ (quote (7 4 3 9)) (quote (6 2 6 2)))  
(13 6 9 2)  
> (+ (quote (1 2 3 4)) (list (+ 2 2) 3 (/ 4 2) 1))  
(5 5 5.0 5)
```

